



NORDFLEX

F0901

UNIVERSAL POLYESTER PUTTY

VERSION: 121212

DEFINITION

Polyester putty for bodywork. Formulated to enable fast repairs, it has excellent adhesion to metal and a high filling power that allows it to level large defects. Its thixotropy ensures an easy application to awkward areas.

PHYSICAL CHARACTERISTICS

Nature: Unsaturated polyester
Colour: Cream
Specific weight: 1,9 kg/l at 20°C
VOC: 50 g/l Mixing Application

AUXILIARY PRODUCTS




Hardener PBO

SUITABLE SURFACES

It may be applied on steel and polyester surfaces.
When maximum protection is required apply on epoxy primer.
Do not apply on thermoplastic finishes and Wash Primers.

SURFACE PREPARATION

- 1 - Identify surface.
- 2 - Process:

PROCESS		Steel	Polyester UP-GFK
	P80	✓	✓
	P150	✓	✓
	Cleaning thinner	✓	✓










NORDFLEX

F0901 UNIVERSAL POLYESTER PUTTY

1 – APPLICATION

2 – SANDING

	 WEIGHT	 100		 TIME	 ORBIT			
10°C	100:2	6,5'	30'	5 min	INITIAL	7 - 5 mm	P120	P80
20°C		5'	20'	DISTANCE 80 cm				P150
30°C		3,5'	15'	MAX. T 80°C				FINAL

REMARKS

Do not add more hardener than specified. Mix thoroughly.
It must be isolated before applying finish coating.
Polyester putties will not harden at temperatures under +5°C.

EQUIPMENT CLEANING

Clean putty knives with a cleaning thinner before the product hardens.

SAFETY

Follow instructions of product label. For more information check the Safety Data Sheets. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

GUARANTEE

In unopened original packaging, one year from manufacturing date.

SUGGESTION:

Dry sanding on polyester putties is always recommended because the dampness retained in the putty during wet sanding might cause problems in the support as well as in the finishing.

For any technical information contact with our Customer Attention Service or our Technical Department.
UAB Svydis declines any responsibility due to an incorrect use of the product.